

FAG 33013参数

尺寸	$r_{3, 4 \text{ min}}$	1.5	mm	-
	$r_{a \text{ max}}$	1.5	mm	-
	$r_{b \text{ max}}$	1.5	mm	-
重量	m	766	g	质量
基本额定载荷	C_r	100000	N	基本额定动载荷, 径向
	C_{0r}	161000	N	基本额定静载荷, 径向
计算系数	e	0.35		-
	Y	1.72		-
	Y_0	0.95		-
疲劳极限载荷	C_{ur}	20300	N	疲劳极限载荷, 径向
极限转速	n_G	6900	r/min	极限转速
参考转速	n_B	4300	r/min	参考速度
说明		T2CE065		根据 DIN ISO 355 的 对应型号
尺寸	d	65	mm	-
	D	100	mm	-
	T	27	mm	-
	a	21	mm	-
	$d_{a \text{ max}}$	72	mm	-
	$d_{b \text{ min}}$	72	mm	-
	$r_{1, 2 \text{ min}}$	1.5	mm	-
	B	27	mm	-
	C	21	mm	-
	$C_{a \text{ min}}$	5	mm	-
	$C_{b \text{ min}}$	6	mm	-
	$D_{a \text{ max}}$	93	mm	-
	$D_{a \text{ min}}$	89	mm	-
	$D_{b \text{ min}}$	96	mm	-

FAG 33013图片

