

NSK CRE-12参数

| | | | | |
|---------|-------|--------|-------|--------|
| 尺寸 | B2 | 22.22 | mm | - |
| | B3 | 6.35 | mm | - |
| | M2 | 2.4 | mm | - |
| | M1 | 4.8 | mm | - |
| 基本额定载荷 | CR | 8850 | N | 动载荷 |
| | CR2 | 900 | kgf | 动载荷 |
| 极限载荷 | PMAX | 5900 | N | 极限载荷 |
| | PMAX2 | 600 | kgf | 极限载荷 |
| 滚轮极限载荷 | LTL | 4550 | N | 滚轮极限载荷 |
| 重量 | MASS | 34 | g | 重量 |
| 六角形孔的尺寸 | X | 0.00 | mm | 双边距离 |
| 偏心轴衬尺寸 | B4 | 12.70 | mm | - |
| | SD1 | 12.700 | mm | - |
| | E | 0.38 | mm | - |
| 挡肩尺寸 | F | 12.7 | mm | (最小) |
| 拧紧力矩 | TT | 630 | n. cm | (最大) |
| 型号 | 型号 | CRE-12 | | - |
| 外形尺寸 | D | 19.050 | mm | 外径 |
| | C | 12.70 | mm | 宽度 |
| | SD | 9.525 | mm | 外径 |
| 尺寸 | G | 3/8-24 | mm | 螺栓 |
| | G1 | 9.5 | mm | - |
| | B1 | 36.1 | mm | - |

NSK CRE-12图片





CRE

参考资料:<http://www.sozhou.com/p/9bda7664.html>

