

FAG 32308-B参数

尺寸	d	40	mm	-	
	D	90	mm	-	
	T	35.25	mm	-	
	a	28	mm	-	
	B	33	mm	-	
	C	27	mm	-	
	$C_{a \min}$	4	mm	-	
	$C_{b \min}$	8	mm	-	
	$D_{a \max}$	81	mm	-	
	$D_{a \min}$	69	mm	-	
	$D_{b \min}$	85	mm	-	
	d_1	67	mm	-	
	$d_{a \max}$	50	mm	-	
	$d_{b \min}$	49	mm	-	
	$r_{1, 2 \min}$	2	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	2	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	1180	g	质量
	基本额定载荷	C_r	120000	N	基本额定动载荷, 径向
C_{0r}		149000	N	基本额定静载荷, 径向	
计算系数	e	0.55		-	
	Y	1.1		-	
	Y_0	0.6		-	
疲劳极限载荷	C_{ur}	18200	N	疲劳极限载荷, 径向	
极限转速	n_G	8000	r/min	极限转速	
参考转速	n_B	5500	r/min	参考速度	

FAG 32308-B图片

