

FAG 23956-K-MB + H3956参数

尺寸	d	280	mm	-
	d <sub>a max</sub>	303	mm	-
	d <sub>b min</sub>	290	mm	-
	d <sub>s</sub>	8	mm	-
	l	121	mm	-
	n <sub>s</sub>	15	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
说明		H3956		质量, 紧定套
重量	m	24700	g	质量
	m <sub>1</sub>	15600	g	质量, 紧定套
基本额定载荷	C <sub>r</sub>	970000	N	基本额定动载荷, 径向
计算系数	e	0.18		-
	Y <sub>1</sub>	3.76		-
	Y <sub>2</sub>	5.59		-
基本额定载荷	C <sub>0r</sub>	2040000	N	基本额定静载荷, 径向
计算系数	Y <sub>0</sub>	3.67		-
极限转速	n <sub>G</sub>	2000	r/min	极限转速
参考转速	n <sub>B</sub>	1100	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	129000	N	疲劳极限载荷, 径向
尺寸	d <sub>1H</sub>	260	mm	-
	D	380	mm	-
	B	75	mm	-
	B <sub>a min</sub>	12	mm	-
	c	38	mm	-
	c <sub>1</sub>	49	mm	-
	D <sub>1</sub>	350	mm	-

$D_{a \max}$	369.8	mm	-
$D_m$	330	mm	-

FAG 23956-K-MB + H3956图片

