

FAG HCB71921-E-T-P4S参数

| | | | | |
|--------|--------------------|-------|-------|-------------|
| 尺寸 | d | 105 | mm | - |
| | D | 145 | mm | - |
| | B | 20 | mm | - |
| | a | 39 | mm | - |
| | D_a H12 | 138 | mm | - |
| | d_a h12 | 112 | mm | - |
| | $r_{1\ min}$ | 1.1 | mm | - |
| | $r_{a\ max}$ | 0.6 | mm | - |
| | $r_{al\ max}$ | 0.6 | mm | - |
| | r_{\min} | 1.1 | mm | - |
| | 重量 | m | 685 | g |
| 基本额定载荷 | C_r | 57000 | N | 基本额定动载荷，径向 |
| | C_{0r} | 30000 | N | 基本额定静载荷，径向 |
| 系数 | f_0 | 11.5 | | - |
| 极限转速 | $n_{G\ Fett}$ | 11000 | r/min | 脂润滑时的极限转速 |
| | $n_{G\ \ddot{o}l}$ | 17000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 2800 | N | 疲劳极限载荷，径向 |

FAG HCB71921-E-T-P4S图片



