

### FAG 33022参数

尺寸	$C_{b \min}$	10	mm	-
	$D_{a \max}$	160	mm	-
	$D_{a \min}$	152	mm	-
	$D_{b \min}$	161	mm	-
	$d_1$	139.2	mm	-
	$d_{a \max}$	123	mm	-
	$d_{b \min}$	120	mm	-
	$r_{1, 2 \min}$	2.5	mm	-
	$r_{3, 4 \min}$	2	mm	-
	$r_{a \max}$	2.5	mm	-
	$r_{b \max}$	2	mm	-
重量	m	4160	g	质量
基本额定载荷	$C_r$	295000	N	基本额定动载荷, 径向
	$C_{0r}$	520000	N	基本额定静载荷, 径向
计算系数	e	0.29		-
	Y	2.09		-
	$Y_0$	1.15		-
疲劳极限载荷	$C_{ur}$	61000	N	疲劳极限载荷, 径向
极限转速	$n_G$	3950	r/min	极限转速
参考转速	$n_B$	2750	r/min	参考速度
尺寸	d	110	mm	-
	D	170	mm	-
	T	47	mm	-
	a	33	mm	-
	B	47	mm	-
	C	37	mm	-
	$C_{a \min}$	7	mm	-

FAG 33022图片

