

FAG 24184-B-K30 + AH24184参数

疲劳极限载荷	C_{ur}	980000	N	疲劳极限载荷，径向	
尺寸	d_{1H}	400	mm	-	
	D	700	mm	-	
	B	280	mm	-	
	a	22	mm	-	
	b	30	mm	-	
	D_1	590.3	mm	-	
	$D_{a\ max}$	674	mm	-	
	d	420	mm	-	
	d_{2G}	Tr440x5		-	
	$d_{a\ min}$	446	mm	-	
	d_s	12.5	mm	-	
	l	310	mm	-	
	n_s	23.5	mm	-	
	$r_{a\ max}$	5	mm	-	
	r_{min}	6	mm	-	
	说明		AH24184		型号，退卸套
	重量	m	407000	g	质量
m_1		41000	g	质量，退卸套	
基本额定载荷	C_r	6200000	N	基本额定动载荷，径向	
计算系数	e	0.4		-	
	Y_1	1.67		-	
	Y_2	2.49		-	
基本额定载荷	C_{0r}	12700000	N	基本额定静载荷，径向	
计算系数	Y_0	1.63		-	
极限转速	n_G	730	r/min	极限转速	
参考转速	n_B	270	r/min	参考速度	

FAG 24184-B-K30 + AH24184图片



参考资料:<http://www.sozhou.com/p/b709b025.html>