

FAG 30222-A参数

尺寸	$C_{a \min}$	6	mm	-
	$C_{b \min}$	9	mm	-
	$D_{a \max}$	188	mm	-
	$D_{a \min}$	174	mm	-
	$D_{b \min}$	187	mm	-
	d_1	148.7	mm	-
	$d_{a \max}$	129	mm	-
	$d_{b \min}$	122	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	5230	g	质量
基本额定载荷	C_r	315000	N	基本额定动载荷, 径向
	C_{0r}	415000	N	基本额定静载荷, 径向
计算系数	e	0.42		-
	Y	1.43		-
	Y_0	0.79		-
疲劳极限载荷	C_{ur}	45500	N	疲劳极限载荷, 径向
极限转速	n_G	3550	r/min	极限转速
参考转速	n_B	2550	r/min	参考速度
说明		T3FB110		根据 DIN ISO 355 的 对应型号
尺寸	d	110	mm	-
	D	200	mm	-
	T	41	mm	-
	a	39	mm	-
	B	38	mm	-

FAG 30222-A图片

