

FAG NU411-M1参数

| | | | | |
|--------|---------------------|--------|-------|-------------|
| 尺寸 | d | 55 | mm | - |
| | D | 140 | mm | - |
| | B | 33 | mm | - |
| | D ₁ | 110.7 | mm | - |
| | D _{a max} | 126 | mm | - |
| | d _{a max} | 76 | mm | - |
| | d _{a min} | 69 | mm | - |
| | d _{b min} | 79 | mm | - |
| | E | 117.2 | mm | - |
| | F | 77.2 | mm | - |
| | r _{1 min} | 2.1 | mm | - |
| | r _{a max} | 2 | mm | - |
| | r _{al max} | 2 | mm | - |
| | r _{min} | 2.1 | mm | - |
| | s | 3.3 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 2830 | g | 质量 |
| 基本额定载荷 | C _r | 187000 | N | 基本额定动载荷，径向 |
| | C _{0r} | 164000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 8200 | r/min | 极限转速 |
| 参考转速 | n _B | 5100 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 21900 | N | 疲劳极限载荷，径向 |

FAG NU411-M1图片



参考资料:<http://www.sozhou.com/p/c13f992d.html>

