


FAG 292/670-E-MB参数

尺寸	d	670	mm	-
	D	900	mm	-
	T	140	mm	-
	A	364	mm	-
	D <sub>1</sub>	773	mm	-
	D <sub>a max</sub>	836	mm	-
	D <sub>b min</sub>	915	mm	-
	d <sub>1</sub>	855	mm	-
	d <sub>a min</sub>	775	mm	-
	d <sub>b max</sub>	710	mm	-
	r <sub>a max</sub>	5	mm	-
	r <sub>min</sub>	6	mm	-
	T <sub>1</sub>	74	mm	-
	T <sub>2</sub>	50	mm	-
	T <sub>3</sub>	81	mm	-
	T <sub>4</sub>	93	mm	-
重量	m	228500	g	质量
基本额定载荷	C <sub>a</sub>	4700000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	25000000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	640	r/min	极限转速
参考转速	n <sub>B</sub>	375	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	1180000	N	疲劳极限载荷, 轴向

FAG 292/670-E-MB图片



参考资料:<http://www.sozhou.com/p/c412da99.html>