

NACHI E32048J参数

| | | | | |
|--------|--------------|---------|-------|------|
| 外形尺寸 | d | 240 | mm | 内径 |
| | D | 360 | mm | 外径 |
| | B | 76 | mm | 宽度 |
| | T | 76 | mm | 宽度 |
| | C | 57 | mm | 宽度 |
| | r | 4~5.5 | mm | 径向 |
| | r | 4~7.5 | mm | 径向 |
| | 载荷中心 | a | -2.5 | mm |
| 安装尺寸 | da(min) | 258 | mm | (最小) |
| | db(max) | 261 | mm | (最大) |
| | Da(min) | 318 | mm | (最小) |
| | Db(min) | 346 | mm | (最小) |
| | S1(min) | 12 | mm | (最小) |
| | S2(min) | 19 | mm | (最小) |
| | Cone ra(max) | 3 | mm | 内圈 |
| | Cup ra(max) | 2.5 | mm | 外圈 |
| 重量 | Mass | 26800 | g | 重量 |
| 基本额定载荷 | Cr | 924000 | N | 动载荷 |
| | Cor | 1720000 | N | 静载荷 |
| 极限速度 | Grease | 870 | r/min | 脂润滑 |
| | Oil | 1300 | r/min | 油润滑 |

NACHI E32048J图片

参考资料:<http://www.sozhou.com/p/c471a329.html>

