



### FAG 29338-E1参数

尺寸	d	190	mm	-	
	D	320	mm	-	
	T	78	mm	-	
	A	110	mm	-	
	D <sub>1</sub>	243.5	mm	-	
	D <sub>a max</sub>	281	mm	-	
	D <sub>b min</sub>	325	mm	-	
	d <sub>1</sub>	290.1	mm	-	
	d <sub>a min</sub>	250	mm	-	
	d <sub>b max</sub>	201	mm	-	
	d <sub>b1 max</sub>	211	mm	-	
	r <sub>a max</sub>	3	mm	-	
	r <sub>min</sub>	4	mm	-	
	T <sub>1</sub>	36	mm	-	
	T <sub>3</sub>	49	mm	-	
	T <sub>5</sub>	70	mm	-	
	重量	m	22300	g	质量
	基本额定载荷	C <sub>a</sub>	1680000	N	基本额定动载荷, 轴向
		C <sub>0a</sub>	4850000	N	基本额定静载荷, 轴向
	极限转速	n <sub>G</sub>	2060	r/min	极限转速
参考转速	n <sub>B</sub>	1090	r/min	参考速度	
疲劳极限载荷	C <sub>ua</sub>	590000	N	疲劳极限载荷, 轴向	

### FAG 29338-E1图片



参考资料: <http://www.sozhou.com/p/c7c89da0.html>

