



FAG NJ2324-E-M1 + HJ2324-E参数

尺寸	d	120	mm	-	
	D	260	mm	-	
	B	86	mm	-	
	B ₁	14	mm	-	
	B ₂	26	mm	-	
	D ₁	218.7	mm	-	
	D _{a max}	246	mm	-	
	d ₁	168.1	mm	-	
	d _{a max}	151	mm	-	
	d _{a min}	134	mm	-	
	d _{c min}	171	mm	-	
	E	230	mm	-	
	F	154	mm	-	
	r _{1 min}	3	mm	-	
	r _{a max}	2.5	mm	-	
	r _{al max}	2.5	mm	-	
	r _{min}	3	mm	-	
	s	7.2	mm	距离中心位置的轴向偏移	
	说明		HJ2324-E		型号, L 型圈
	重量	m	23800	g	质量
m ₁		1490	g	质量, L 型圈	
基本额定载荷	C _r	930000	N	基本额定动载荷, 径向	
	C _{0r}	1010000	N	基本额定静载荷, 径向	
极限转速	n _G	3950	r/min	极限转速	
参考转速	n _B	2010	r/min	参考速度	
疲劳极限载荷	C _{ur}	166000	N	疲劳极限载荷, 径向	

FAG NJ2324-E-M1 + HJ2324-E图片



参考资料:<http://www.sozhou.com/p/c7d8a87e.html>

