

FAG 24138-E1参数

| | | | | |
|--------|--------------------|---------|-------|------------|
| 尺寸 | d | 190 | mm | - |
| | D | 320 | mm | - |
| | B | 128 | mm | - |
| | D ₁ | 271.2 | mm | - |
| | d ₂ | 217.4 | mm | - |
| | d _s | 6.3 | mm | - |
| | n _s | 12.2 | mm | - |
| | r _{a max} | 2.5 | mm | - |
| | r _{min} | 3 | mm | - |
| 重量 | m | 41500 | g | 质量 |
| 基本额定载荷 | C _r | 1680000 | N | 基本额定动载荷，径向 |
| 计算系数 | e | 0.37 | | - |
| | Y ₁ | 1.82 | | - |
| | Y ₂ | 2.7 | | - |
| 基本额定载荷 | C _{0r} | 2550000 | N | 基本额定静载荷，径向 |
| 计算系数 | Y ₀ | 1.78 | | - |
| 极限转速 | n _G | 1850 | r/min | 极限转速 |
| 参考转速 | n _B | 900 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 226000 | N | 疲劳极限载荷，径向 |

FAG 24138-E1图片



参考资料:<http://www.sozhou.com/p/cab4190c.html>