

## FAG 24130-E1参数

|        |                    |         |       |            |
|--------|--------------------|---------|-------|------------|
| 尺寸     | d                  | 150     | mm    | -          |
|        | D                  | 250     | mm    | -          |
|        | B                  | 100     | mm    | -          |
|        | D <sub>1</sub>     | 213     | mm    | -          |
|        | d <sub>2</sub>     | 170.3   | mm    | -          |
|        | d <sub>s</sub>     | 4.8     | mm    | -          |
|        | n <sub>s</sub>     | 9.5     | mm    | -          |
|        | r <sub>a max</sub> | 2.1     | mm    | -          |
|        | r <sub>min</sub>   | 2.1     | mm    | -          |
| 重量     | m                  | 20600   | g     | 质量         |
| 基本额定载荷 | C <sub>r</sub>     | 1050000 | N     | 基本额定动载荷，径向 |
| 计算系数   | e                  | 0.37    |       | -          |
|        | Y <sub>1</sub>     | 1.83    |       | -          |
|        | Y <sub>2</sub>     | 2.72    |       | -          |
| 基本额定载荷 | C <sub>0r</sub>    | 1520000 | N     | 基本额定静载荷，径向 |
| 计算系数   | Y <sub>0</sub>     | 1.79    |       | -          |
| 极限转速   | n <sub>G</sub>     | 2370    | r/min | 极限转速       |
| 参考转速   | n <sub>B</sub>     | 1280    | r/min | 参考速度       |
| 疲劳极限载荷 | C <sub>ur</sub>    | 148000  | N     | 疲劳极限载荷，径向  |

## FAG 24130-E1图片



参考资料:<http://www.sozhou.com/p/cb69c19a.html>