

FAG 32318-A参数

尺寸	B	64	mm	-	
	C	53	mm	-	
	$C_{a \min}$	8	mm	-	
	$C_{b \min}$	14.5	mm	-	
	$D_{a \max}$	176	mm	-	
	$D_{a \min}$	157	mm	-	
	$D_{b \min}$	177	mm	-	
	d_1	137.4	mm	-	
	$d_{a \max}$	108	mm	-	
	$d_{b \min}$	104	mm	-	
	$r_{1, 2 \min}$	4	mm	-	
	$r_{3, 4 \min}$	3	mm	-	
	$r_{a \max}$	4	mm	-	
	$r_{b \max}$	3	mm	-	
	重量	m	8510	g	质量
	基本额定载荷	C_r	485000	N	基本额定动载荷，径向
C_{0r}		660000	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	Y_0	0.96		-	
疲劳极限载荷	C_{ur}	75000	N	疲劳极限载荷，径向	
极限转速	n_G	3700	r/min	极限转速	
参考转速	n_B	2750	r/min	参考速度	
说明		T2GD090		根据 DIN ISO 355 的 对应型号	
尺寸	d	90	mm	-	
	D	190	mm	-	
	T	67.5	mm	-	

FAG 32318-A图片

