

FAG 23092-B-K-MB + AHX3092G参数

尺寸	d_{1H}	440	mm	-	
	D	680	mm	-	
	B	163	mm	-	
	a	11	mm	-	
	b	37	mm	-	
	D_1	612.2	mm	-	
	$D_{a\ max}$	657	mm	-	
	d	460	mm	-	
	d_{2G}	Tr480x5		-	
	$d_{a\ min}$	483	mm	-	
	d_s	12.5	mm	-	
	l	202	mm	-	
	n_s	23.5	mm	-	
	$r_{a\ max}$	5	mm	-	
	r_{min}	6	mm	-	
	说明		AHX3092G		型号, 退卸套
	重量	m	212000	g	质量
m_1		32900	g	质量, 退卸套	
基本额定载荷	C_r	3650000	N	基本额定动载荷, 径向	
计算系数	e	0.24		-	
	Y_1	2.84		-	
	Y_2	4.23		-	
基本额定载荷	C_{0r}	7650000	N	基本额定静载荷, 径向	
计算系数	Y_0	2.78		-	
极限转速	n_G	970	r/min	极限转速	
参考转速	n_B	580	r/min	参考速度	
疲劳极限载荷	C_{ur}	440000	N	疲劳极限载荷, 径向	

FAG 23092-B-K-MB + AHX3092G图片



参考资料:<http://www.sozhou.com/p/d0ba782d.html>