

FAG NU2218-E-TVP2参数

| | | | | |
|--------|---------------------|--------|-------|-------------|
| 尺寸 | d | 90 | mm | - |
| | D | 160 | mm | - |
| | B | 40 | mm | - |
| | D ₁ | 139.7 | mm | - |
| | D _{a max} | 149 | mm | - |
| | d _{a max} | 105 | mm | - |
| | d _{a min} | 101 | mm | - |
| | d _{b min} | 109 | mm | - |
| | E | 145 | mm | - |
| | F | 107 | mm | - |
| | r _{1 min} | 2 | mm | - |
| | r _{a max} | 2 | mm | - |
| | r _{al max} | 2 | mm | - |
| | r _{min} | 2 | mm | - |
| | s | 2.5 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 3170 | g | 质量 |
| 基本额定载荷 | C _r | 285000 | N | 基本额定动载荷，径向 |
| | C _{0r} | 315000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 5200 | r/min | 极限转速 |
| 参考转速 | n _B | 3300 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 56000 | N | 疲劳极限载荷，径向 |

FAG NU2218-E-TVP2图片



参考资料:<http://www.sozhou.com/p/d1a89299.html>

