

FAG 32230-A参数

尺寸	d	150	mm	-
	D	270	mm	-
	T	77	mm	-
	a	64	mm	-
	B	73	mm	-
	C	60	mm	-
	$C_{a \min}$	8	mm	-
	$C_{b \min}$	17	mm	-
	$D_{a \max}$	256	mm	-
基本额定载荷	C_r	740000	N	基本额定动载荷，径向
	C_{0r}	1150000	N	基本额定静载荷，径向
计算系数	e	0.44		-
	Y	1.38		-
	Y_0	0.76		-
疲劳极限载荷	C_{ur}	137000	N	疲劳极限载荷，径向
极限转速	n_G	2490	r/min	极限转速
参考转速	n_B	1570	r/min	参考速度
说明		T4GD150		根据 DIN ISO 355 的 对应型号
尺寸	$D_{a \min}$	226	mm	-
	$D_{b \min}$	254	mm	-
	d_1	206.7	mm	-
	$d_{a \max}$	171	mm	-
重量	m	18200	g	质量
尺寸	$d_{b \min}$	164	mm	-
	$r_{1, 2 \min}$	4	mm	-
	$r_{3, 4 \min}$	3	mm	-
	$r_{a \max}$	4	mm	-

FAG 32230-A图片

