

FAG B7004-C-T-P4S参数

| | | | | |
|--------|----------------------|-------|-------|-------------|
| 基本额定载荷 | C_r | 10300 | N | 基本额定动载荷，径向 |
| | C_{0r} | 4250 | N | 基本额定静载荷，径向 |
| 极限转速 | $n_G \text{ Fett}$ | 38000 | r/min | 脂润滑时的极限转速 |
| | $n_G \text{ Öl}$ | 60000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 435 | N | 疲劳极限载荷，径向 |
| 尺寸 | d | 20 | mm | - |
| | D | 42 | mm | - |
| | B | 12 | mm | - |
| | a | 10 | mm | - |
| | $D_a \text{ H12}$ | 37 | mm | - |
| | $d_a \text{ h12}$ | 25 | mm | - |
| | $r_{1 \text{ min}}$ | 0.6 | mm | - |
| | $r_{a \text{ max}}$ | 0.6 | mm | - |
| | $r_{al \text{ max}}$ | 0.3 | mm | - |
| | r_{min} | 0.6 | mm | - |
| 重量 | m | 67 | g | 质量 |

FAG B7004-C-T-P4S图片



