

FAG 33209参数

尺寸	d	45	mm	-	
	D	85	mm	-	
	T	32	mm	-	
	a	22	mm	-	
	B	32	mm	-	
	C	25	mm	-	
	$C_{a \min}$	5	mm	-	
	$C_{b \min}$	7	mm	-	
	$D_{a \max}$	78	mm	-	
	$D_{a \min}$	72	mm	-	
	$D_{b \min}$	81	mm	-	
	d_1	66.2	mm	-	
	$d_{a \max}$	52	mm	-	
	$d_{b \min}$	52	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	895	g	质量
	基本额定载荷	C_r	107000	N	基本额定动载荷，径向
C_{0r}		146000	N	基本额定静载荷，径向	
计算系数	e	0.39		-	
	Y	1.56		-	
	Y_0	0.86		-	
疲劳极限载荷	C_{ur}	18300	N	疲劳极限载荷，径向	
极限转速	n_G	8200	r/min	极限转速	
参考转速	n_B	5200	r/min	参考速度	

FAG 33209图片

