

FAG 30310-A参数

疲劳极限载荷	C_{ur}	17700	N	疲劳极限载荷，径向	
极限转速	n_G	6800	r/min	极限转速	
参考转速	n_B	4800	r/min	参考速度	
说明		T2FB050		根据 DIN ISO 355 的 对应型号	
尺寸	d	50	mm	-	
	D	110	mm	-	
	T	29.25	mm	-	
	a	23	mm	-	
	B	27	mm	-	
	C	23	mm	-	
	$C_{a \min}$	4	mm	-	
	$C_{b \min}$	6	mm	-	
	$D_{a \max}$	100	mm	-	
	$D_{a \min}$	95	mm	-	
	$D_{b \min}$	102	mm	-	
	d_1	77.6	mm	-	
	$d_{a \max}$	65	mm	-	
	$d_{b \min}$	60	mm	-	
	$r_{1, 2 \min}$	2.5	mm	-	
	$r_{3, 4 \min}$	2	mm	-	
	$r_{a \max}$	2.5	mm	-	
	$r_{b \max}$	2	mm	-	
	重量	m	1380	g	质量
	基本额定载荷	C_r	130000	N	基本额定动载荷，径向
C_{0r}		148000	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.74		-	

FAG 30310-A图片

