

**FAG 294/600-E-MB参数**

尺寸	d	600	mm	-
	D	1030	mm	-
	T	258	mm	-
	A	347	mm	-
	D <sub>1</sub>	782	mm	-
	D <sub>a max</sub>	900	mm	-
	D <sub>b min</sub>	1055	mm	-
	d <sub>1</sub>	940	mm	-
	d <sub>a min</sub>	800	mm	-
	d <sub>b max</sub>	653	mm	-
	r <sub>a max</sub>	10	mm	-
	r <sub>min</sub>	12	mm	-
	T <sub>1</sub>	127	mm	-
	T <sub>2</sub>	93	mm	-
	T <sub>3</sub>	162	mm	-
	T <sub>4</sub>	182	mm	-
	重量	m	829100	g
基本额定载荷	C <sub>a</sub>	12200000	N	基本额定动载荷, 轴向
	C <sub>0a</sub>	51000000	N	基本额定静载荷, 轴向
极限转速	n <sub>G</sub>	455	r/min	极限转速
参考转速	n <sub>B</sub>	280	r/min	参考速度
疲劳极限载荷	C <sub>ua</sub>	2550000	N	疲劳极限载荷, 轴向

**FAG 294/600-E-MB图片**



参考资料:<http://www.sozhou.com/p/f37f1aca.html>