

FAG 23188-K-MB参数

| | | | | |
|--------|--------------------|----------|-------|------------|
| 尺寸 | d | 440 | mm | - |
| | D | 720 | mm | - |
| | B | 226 | mm | - |
| | D ₁ | 626 | mm | - |
| | D _{a max} | 694 | mm | - |
| | d _{a min} | 466 | mm | - |
| | d _s | 12.5 | mm | - |
| | n _s | 23.5 | mm | - |
| | r _{a max} | 5 | mm | - |
| | r _{min} | 6 | mm | - |
| 重量 | m | 378000 | g | 质量 |
| 基本额定载荷 | C _r | 5200000 | N | 基本额定动载荷，径向 |
| 计算系数 | e | 0.32 | | - |
| | Y ₁ | 2.1 | | - |
| | Y ₂ | 3.13 | | - |
| 基本额定载荷 | C _{0r} | 10400000 | N | 基本额定静载荷，径向 |
| 计算系数 | Y ₀ | 2.06 | | - |
| 极限转速 | n _G | 820 | r/min | 极限转速 |
| 参考转速 | n _B | 430 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 485000 | N | 疲劳极限载荷，径向 |

FAG 23188-K-MB图片





参考资料:<http://www.sozhou.com/p/f6d7d866.html>