

## FAG 33014参数

尺寸	d	70	mm	-
	D	110	mm	-
	$C_b \text{ min}$	5.5	mm	-
	$D_a \text{ max}$	103	mm	-
	$D_a \text{ min}$	99	mm	-
	$D_b \text{ min}$	105	mm	-
	$d_1$	91	mm	-
	$d_a \text{ max}$	78	mm	-
	$d_b \text{ min}$	77	mm	-
	$r_{1, 2} \text{ min}$	1.5	mm	-
	$r_{3, 4} \text{ min}$	1.5	mm	-
	$r_a \text{ max}$	1.5	mm	-
	$r_b \text{ max}$	1.5	mm	-
	重量	m	1140	g
基本额定载荷	$C_r$	136000	N	基本额定动载荷, 径向
	$C_{0r}$	223000	N	基本额定静载荷, 径向
计算系数	e	0.28		-
	Y	2.11		-
	$Y_0$	1.16		-
疲劳极限载荷	$C_{ur}$	28500	N	疲劳极限载荷, 径向
极限转速	$n_G$	6200	r/min	极限转速
参考转速	$n_B$	3900	r/min	参考速度
说明		T2CE070		根据 DIN ISO 355 的 对应型号
尺寸	T	31	mm	-
	a	22	mm	-
	B	31	mm	-
	C	25.5	mm	-

## FAG 33014图片

