

FAG 32309-BA参数

| | | | | | |
|-----------------|-----------------------|----------------|--------|-------------|-------------|
| 尺寸 | d | 45 | mm | - | |
| | D | 100 | mm | - | |
| | T | 38.25 | mm | - | |
| | a | 30 | mm | - | |
| | B | 36 | mm | - | |
| | C | 30 | mm | - | |
| | C _{a min} | 5 | mm | - | |
| | C _{b min} | 8 | mm | - | |
| | D _{a max} | 91 | mm | - | |
| | D _{a min} | 76 | mm | - | |
| | D _{b min} | 94 | mm | - | |
| | d ₁ | 74.2 | mm | - | |
| | d _{a max} | 55 | mm | - | |
| | d _{b min} | 54 | mm | - | |
| | r _{1, 2 min} | 2 | mm | - | |
| | r _{3, 4 min} | 1.5 | mm | - | |
| | r _{a max} | 2 | mm | - | |
| | r _{b max} | 1.5 | mm | - | |
| | 重量 | m | 1480 | g | 质量 |
| | 基本额定载荷 | C _r | 144000 | N | 基本额定动载荷, 径向 |
| C _{0r} | | 187000 | N | 基本额定静载荷, 径向 | |
| 计算系数 | e | 0.55 | | - | |
| | Y | 1.1 | | - | |
| | Y ₀ | 0.6 | | - | |
| 疲劳极限载荷 | C _{ur} | 23100 | N | 疲劳极限载荷, 径向 | |
| 极限转速 | n _G | 7200 | r/min | 极限转速 | |
| 参考转速 | n _B | 5000 | r/min | 参考速度 | |

FAG 32309-BA图片

