

## FAG 32944参数

尺寸	$D_{a \max}$	288	mm	-
	$D_{a \min}$	275	mm	-
	$D_{b \min}$	290	mm	-
	$d_1$	260	mm	-
	$d_{a \max}$	234	mm	-
	$d_{b \min}$	232	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	10200	g	质量
基本额定载荷	$C_r$	495000	N	基本额定动载荷, 径向
	$C_{0r}$	980000	N	基本额定静载荷, 径向
计算系数	e	0.43		-
	Y	1.41		-
	$Y_0$	0.78		-
疲劳极限载荷	$C_{ur}$	110000	N	疲劳极限载荷, 径向
极限转速	$n_G$	2150	r/min	极限转速
参考转速	$n_B$	1280	r/min	参考速度
说明		T3EC220		根据 DIN ISO 355 的 对应型号
尺寸	d	220	mm	-
	D	300	mm	-
	T	51	mm	-
	a	59	mm	-
	B	51	mm	-
	C	39	mm	-
	$C_{a \min}$	9	mm	-

FAG 32944图片

