

### FAG HCB7032-C-T-P4S参数

|        |                    |        |       |             |
|--------|--------------------|--------|-------|-------------|
| 尺寸     | d                  | 160    | mm    | -           |
|        | D                  | 240    | mm    | -           |
|        | B                  | 38     | mm    | -           |
|        | a                  | 46     | mm    | -           |
|        | $D_a$ H12          | 228    | mm    | -           |
|        | $d_a$ h12          | 174    | mm    | -           |
|        | $r_1$ min          | 2.1    | mm    | -           |
|        | $r_a$ max          | 2      | mm    | -           |
|        | $r_{al}$ max       | 1      | mm    | -           |
|        | $r_{min}$          | 2.1    | mm    | -           |
| 重量     | m                  | 4200   | g     | 质量          |
| 基本额定载荷 | $C_r$              | 192000 | N     | 基本额定动载荷，径向  |
|        | $C_{0r}$           | 102000 | N     | 基本额定静载荷，径向  |
| 极限转速   | $n_{G\ Fett}$      | 7500   | r/min | 脂润滑时的极限转速   |
|        | $n_{G\ \ddot{O}l}$ | 0      | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | $C_{ur}$           | 7500   | N     | 疲劳极限载荷，径向   |

### FAG HCB7032-C-T-P4S图片



